




Aquadeep

"Lighting fixture to be floor-recessed.
Die cast aluminium body.
The IP 67 protection rating allows for
dust-proofing and water-proofing,
even during brief immersions.
Suitable for fitting in damp surroundings,
both indoors and outdoors".



Aquadeep



20 watt "T"
(round)



- METAL HALIDES 20 W
- HIT-TC-CRI - BASE G 8,5
- STAINLESS STEEL RING
- DIE-CAST ALUMINIUM BODY
- HALF FROSTED GLASS (Standard)
- IP 67
- INTEGRATED ELECTRONIC COMPONENTS
- MOVABLE
- SPOT OR FLOOD REFLECTOR (SEE OPTIONS)

Aquadeep

20 watt "Q"
(square)



- FLUO 18 W - TC-T Gx24 d-2
- STAINLESS STEEL RING
- DIE-CAST ALUMINIUM BODY
- HALF FROSTED GLASS (Standard)
- IP 67
- INTEGRATED COMPONENTS


Aquadeep

fluo
18 watt "T"
(round)



Aquadeep

fluo
18 watt "Q"
(square)



↓ MAX 5.000 KGS ↓



Ø 180 mm (180 x 180 mm)

OPTIONS FOR AQUADEEP 20 W "T" AND "Q"



SPOT REFLECTOR 5°
(ON REQUEST)



FLOOD REFLECTOR 23°
(STANDARD)



POLYPROPYLENE
HOUSING FOR RECESS
(Included)